C-Series LED

120V-277V LED Large Flood, 85W



| PROJECT: | | | |
|-----------|--|--|--|
| TYPE: | | | |
| ORDERING: | | | |
| COMMENTS: | | | |
| | | | |
| | | | |
| | | | |

APPLICATIONS

Kichler's 120V-277V LED flood lighting fixtures are designed for outdoor lighting applications requiring uniform light sources, with long life, and little maintenance requirements.

CONSTRUCTION

Modern style with durable polyester powder coating. Vandal resistant hardware, reinforced knuckle design, a water draining front end with an integrated cowl. The accent can accept multiple media; lenses and louvers.

ELECTRICAL

UL listed for 120V-277 VAC (50/60 Hz), and suitable for wet locations. Integrated surge protection (4kV) comes standard.

OPTICS

Utilized a two LED chip-on-board light sources that provides for center-to-edge uniformity and enhances beam control. NEMA 7 x 6 wide flood. Three-step binning for tight color consistency.

INCLUDED ACCESSORIES

Three (3) King Innovation Gel-Filled Wire Nuts

LUMEN INFORMATION

| | | 16225 | 16225 | | | |
|---------|-----|--------|----------|-----------|--|--|
| Wattage | CRI | Lumens | Efficacy | L70 (hrs) | | |
| 85W | 80+ | 7300Lm | 86 LPW | 40,000 | | |

^{*}Lumen values same for both 3000K/4000K

LISTINGS

UL / cUL Listed - Wet Location rated IP66 - Dust & Water proof FCC Compliant

WARRANTY

6 Year Limited Warranty

ADDITIONAL MOUNTING OPTIONS





Slip-Fit Mount

Trunnion Mount

ORDERING MATRIX (Model # +Finish & CCT Codes, Version optional)

| Model # | Wattage | Lumens | Finish | CCT | Version (option) |
|---------|---------|---------|-------------------------------------|------------|------------------|
| 16225 | 85W | 7300 Lm | AZT - Textured Architectural Bronze | 30 - 3000k | TR - Trunnion |
| 16225 | 85W | 7300 Lm | BKT - Textured Black | 40 - 4000k | SL - Slip-Fit |


Example: 16225BKT40SL = 7300Lm Black, Flood, 4000K, Slip-Fit



C-Series LED

120V-277V LED Large Flood, 85W

DIMENSIONS



ACCESSORIES

Ordered & shipped separately (for knuckle only)

15645 AZT, BKT - 6" StemCorrosion resistant15656 AZT, BKT - 12" Stemaluminum alloy with15657 AZT, BKT - 18" Stembaked thermoset15658 AZT, BKT - 24" Stempowder coating.

15276 BKT - Power Post: A Fast, One-Step Connector Made of Impact / Corrosion Resistant PVC 2.250" Inside Diameter to Accommodate Conduits of Different Sizes


Accepts .50 NPSM Thread

Designed For 120V-277V Line Voltage Landscape Lighting, Eliminating Need For Above or Below Ground Boxes.
Built-in Stabilizer Removes Need For Concrete

15601 AZT, BKT - Cast Aluminum Surface Mounting Flange with Bronze or Black Finish, Neoprene Gasket For Watertight Seal

15609 AZT, BKT - Junction Box Mounting Bracket Corrosion Resistant Cast Aluminum Alloy with Baked Thermoset Bronze or Black Powder Coat Finish

PHOTOMETRIC DIAGRAMS



16225BKT30 shown (7300 Lumens)

