

| Project:      |  |  |
|---------------|--|--|
| Fixture Type: |  |  |
| Location:     |  |  |
| Contact:      |  |  |

# P2586 60" Ceiling Fan

Ceiling mounted • Dry location listed PROGRESS LED

### **Description:**

The 60" Glandon ceiling fan features a 17W LED module (3000K color temperature) with a shatterproof white opal shade. With a sophisticated and modern design, Glandon has a dual mount system and comes with a full function remote control- batteries are included.

## **Specifications:**

- · Gilded Iron (-71) (Painted)
- Steel constructionA sophisticated and modern design, the 60" Glandon 6 blade ceiling fan includes reversible blades that will complement any décor
- · Includes Progress Lightings dependable AirPro motor for a smooth, quiet performance
- Features a 17W dimmable, 1400 Lumen, 3000K, 90CRI LED replaceable light module, offering energy- and cost-savings with a shatterproof white opal shade
- 60" fan provides higher airflow making it ideal for extra-large rooms
- Glandon has a dual mount system to offer greater flexibility when installing. The fan can be installed on a flat or sloped ceiling
- A full function 3 speed remote control is included. Conveniently allows you to reverse
  the fan from the remote control
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- · Remote control may be replaced by a P2631-30 wall control
- · Rated for indoor use
- · Limited Lifetime Warranty on the motor for peace of mind
- · Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80" of wire supplied

#### **Performance:**

| Number of Modules   | 1                         |  |
|---------------------|---------------------------|--|
| Input Power         | 18w                       |  |
| Input Voltage       | 120 V                     |  |
| Input Frequency     | 60 Hz                     |  |
| Lumens/LPW          | 1386/77 (LM-79)           |  |
| ССТ                 | 3000 K                    |  |
| CRI                 | 90 CRI                    |  |
| Life (hours)        | 50,000 (L70/TM-21)        |  |
| EMI/RFI             | Title 20                  |  |
| Min. Start Temp     | -10 °C                    |  |
| Max. Operating Temp | 40 °C                     |  |
| Warranty            | Limited Lifetime warranty |  |
| Labels              | UL Dry location listed    |  |

# P2586-7130K

#### Images:



#### **Dimensions:**

Diameter: 60" Height: 17-1/8"