


# TUBE ARCHITECTURAL - model: DS-WD **WAC LIGHTING**

LED Wall Mounts Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## PRODUCT DESCRIPTION

Step inside the world's finest museums, public spaces, corporate offices and luxury homes to see that each of their architectural accents and design elements is showcased with superior grade lighting. The integration of cutting edge designs and advanced technologies is achieved when award-winning WAC luminaires are specified for the next project.

## FEATURES

- IP65 rated, ETL & cETL wet location listed
- Meets 2013 California Title 24 Efficiency
- Energy Star® rated
- ANSI compliant warm/neutral LED bins, for the finest color consistency possible
- Universal driver (120V-220V-277V)
- 0-10V Dimming

## SPECIFICATIONS

- **Rated Life:** 80,000 hours
- **CRI:** Up to 90

Size	Watts	CCT	CRI	Lumens		Lumens			
				Straight Up or Down	Efficacy	Away From the Wall	Towards the Wall	One Side Each	Efficacy
5"	24W x 2	2700K	90	986 x 2	41 Lm/W	1029 x 2	1029 x 2	1029 x 2	45 Lm/W
		2700K	85	1160 x 2	48 Lm/W	1210 x 2	1210 x 2	1210 x 2	50 Lm/W
		3000K	90	1228 x 2	51 Lm/W	1295 x 2	1295 x 2	1295 x 2	56 Lm/W
		3000K	85	1380 x 2	58 Lm/W	1455 x 2	1455 x 2	1455 x 2	61 Lm/W
		3500K	85	1450 x 2	60 Lm/W	1560 x 2	1560 x 2	1560 x 2	65 Lm/W
6"	42W x 2	2700K	90	1522 x 2	36 Lm/W	1914 x 2	1914 x 2	1914 x 2	46 Lm/W
		2700K	85	1790 x 2	43 Lm/W	2200 x 2	2200 x 2	2200 x 2	52 Lm/W
		3000K	90	1793 x 2	43 Lm/W	1873 x 2	1873 x 2	1873 x 2	45 Lm/W
		3000K	85	2015 x 2	48 Lm/W	2230 x 2	2230 x 2	2230 x 2	53 Lm/W
		3500K	85	2110 x 2	50 Lm/W	2445 x 2	2445 x 2	2445 x 2	58 Lm/W
8"	54W x 2	2700K	90	2886 x 2	53 Lm/W	2809 x 2	2809 x 2	2809 x 2	52 Lm/W
		2700K	85	3395 x 2	63 Lm/W	3305 x 2	3305 x 2	3305 x 2	61 Lm/W
		3000K	90	3360 x 2	62 Lm/W	3089 x 2	3089 x 2	3089 x 2	57 Lm/W
		3000K	85	3775 x 2	70 Lm/W	3510 x 2	3510 x 2	3510 x 2	65 Lm/W
		3500K	85	4005 x 2	74 Lm/W	3665 x 2	3665 x 2	3665 x 2	68 Lm/W

## ORDERING NUMBER

Model#	Type	Diameter	Watt	Color Temp	Light Direction	Finish		
<b>DS-WD</b>	Double Sided	5"	24W	<b>927</b> 2700K (90CRI)		<b>BK</b> Black		
				<b>27</b> 2700K			<b>WT</b> White	
				<b>930</b> 3000K (90CRI)				<b>BZ</b> Bronze
				<b>30</b> 3000K				
<b>35</b> 3500K								
	6"	42W	<b>30</b> 3000K					
	8"	54W	<b>30</b> 3000K					
			<b>35</b> 3500K					

**DS-WD**  -   -

Example: **DS-WD08F-30C-WT**

## WAC Lighting

www.waclighting.com  
Phone (800) 526.2588 • Fax (800) 526.2585

## Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050  
Phone (516) 515.5000 • Fax (516) 515.5050

## Western Distribution Center


168 Brea Canyon Road • City of Industry, CA 91789  
Phone (800) 526.2588 • Fax (800) 526.2585

# TUBE ARCHITECTURAL - model: DS-WS

## LED Wall Mounts

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Step inside the world's finest museums, public spaces, corporate offices and luxury homes to see that each of their architectural accents and design elements is showcased with superior grade lighting. The integration of cutting edge designs and advanced technologies is achieved when award-winning WAC luminaires are specified for the next project.

### FEATURES

- IP65 rated, ETL & cETL wet location listed
- Meets 2013 California Title 24 Efficiency
- Energy Star® rated
- Solid aluminum construction
- ANSI compliant warm/neutral LED bins, for the finest color consistency possible
- Universal driver (120V-220V-277V)
- 0-10V Dimming

### SPECIFICATIONS

- **Rated Life:** 80,000 hours
- **CRI:** Up to 90

Size	Watts	CCT	CRI	Lumens		Lumens		
				Straight Up or Down	Efficacy	Away From the Wall	Towards the Wall	Efficacy
5"	24W	2700K	90	986	41 Lm/W	1029	1029	45 Lm/W
		2700K	85	1160	48 Lm/W	1210	1210	50 Lm/W
		3000K	90	1228	51 Lm/W	1295	1295	56 Lm/W
		3000K	85	1380	58 Lm/W	1455	1455	61 Lm/W
		3500K	85	1450	60 Lm/W	1560	1560	65 Lm/W
6"	42W	2700K	90	1522	36 Lm/W	1914	1914	46 Lm/W
		2700K	85	1790	43 Lm/W	2200	2200	52 Lm/W
		3000K	90	1793	43 Lm/W	1873	1873	45 Lm/W
		3000K	85	2015	48 Lm/W	2230	2230	53 Lm/W
		3500K	85	2110	50 Lm/W	2445	2445	58 Lm/W
8"	54W	2700K	90	2886	53 Lm/W	2809	2809	52 Lm/W
		2700K	85	3395	63 Lm/W	3305	3305	61 Lm/W
		3000K	90	3360	62 Lm/W	3089	3089	57 Lm/W
		3000K	85	3775	70 Lm/W	3510	3510	65 Lm/W
		3500K	85	4005	74 Lm/W	3665	3665	68 Lm/W

### ORDERING NUMBER

Model#	Type	Diameter	Watt	Color Temp	Light Direction	Finish	
DS-WS	Single Sided (Dark sky friendly)	05F 06F 08F	5"	24W	927 2700K (90CRI)	<b>S</b> Straight up or down <b>A</b> Away from the wall <b>B</b> Towards the wall	<b>BK</b> Black <b>WT</b> White <b>BZ</b> Bronze <b>GH</b> Graphite
			6"	42W	27 2700K		
			6"	42W	930 3000K (90CRI)		
			8"	54W	30 3000K		
			8"	54W	35 3500K		

DS-WS  -   -

Example: DS-WS06F-30B-BK

### WAC Lighting

www.waclighting.com  
Phone (800) 526.2588 • Fax (800) 526.2585

### Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050  
Phone (516) 515.5000 • Fax (516) 515.5050

### Western Distribution Center

168 Brea Canyon Road • City of Industry, CA 91789  
Phone (800) 526.2588 • Fax (800) 526.2585